

MOTOR MEDIC® AIR BRAKE SYSTEM ANTI-FREEZE & RUST GUARD

Version 1.0

Revision Date: 09/04/2019

SDS Number: 600000001949 Date of last issue: -

Date of first issue: 09/04/2019

SECTION 1. IDENTIFICATION

Product name

: MM AIRBRAKE SYSTEM ANTIFREEZE 4/1GA

Product code

: M2834

Manufacturer or supplier's details

Company name of supplier

: Niteo Products, LLC

Address

Dallas TX 75225

Email Address

: EHS@niteoproducts.com

Telephone

1-844-696-4836

Emergency telephone num-

: 1-800-424-9300 / 1-703-741-5970

Recommended use of the chemical and restrictions on use

Recommended use

: Anti-freezing agents

Restrictions on use

: Use only outdoors or in a well-ventilated area.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids

: Category 2

Acute toxicity (Oral)

Category 3

Acute toxicity (Inhalation)

Category 3

Acute toxicity (Dermal)

Category 3

Specific target organ toxicity

- single exposure

: Category 1 (Central nervous system, Eyes)

GHS label elements Hazard pictograms



Signal word

Danger

Hazard statements

Highly flammable liquid and vapour.



MOTOR MEDIC® AIR BRAKE SYSTEM ANTI-FREEZE & RUST GUARD

Version 1.0

Revision Date:

09/04/2019

SDS Number:

600000001949

Date of last issue: -

Date of first issue: 09/04/2019

Toxic if swallowed, in contact with skin or if inhaled.

Causes damage to organs (Central nervous system, Eyes).

Precautionary statements

Prevention:

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ ventilating/ lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

Wash skin thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/ eye protection/ face protection.

Response:

IF SWALLOWED: Immediately call a POISON CENTER/doctor. Rinse mouth.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor.

IF exposed: Call a POISON CENTER or doctor/ physician.

Take off contaminated clothing and wash before reuse. In case of fire: Use dry sand, dry chemical or alcohol-resistant

foam to extinguish.

Storage:

Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture

Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)	
Methanol	67-56-1	>= 90 - < 100	

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

SECTION 4. FIRST AID MEASURES



MOTOR MEDIC® AIR BRAKE SYSTEM ANTI-FREEZE & RUST GUARD

Version

Revision Date:

SDS Number:

Date of last issue: -

1.0

09/04/2019

600000001949

Date of first issue: 09/04/2019

General advice

Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Do not leave the victim unattended.

If inhaled

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact

If on clothes, remove clothes.

Call a physician or poison control centre immediately.

If on skin, rinse well with water.

In case of eye contact

Flush eyes with water as a precaution.

Remove contact lenses. Protect unharmed eve.

Keep eye wide open while rinsing.

If swallowed

Get medical attention immediately.

Rinse mouth with water.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

Toxic if swallowed, in contact with skin or if inhaled.

Causes damage to organs.

This product contains methanol which can cause intoxication and central nervous system depression. Methanol is metabolized to formic acid and formaldehyde. These metabolites can cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. Ethanol competes for the same metabolic pathway and has been used to prevent methanol metabolism. Ethanol administration is indicated in symptomatic patients or at blood methanol concentrations above 20 ug/dl. Methanol is effectively

removed by hemodialysis.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray

Carbon dioxide (CO2)

Dry chemical

Alcohol-resistant foam

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire-

fighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion prod- : Carbon oxides

ucts



MOTOR MEDIC® AIR BRAKE SYSTEM ANTI-FREEZE & RUST GUARD

Version

Revision Date:

SDS Number:

Date of last issue: -

1.0

09/04/2019

600000001949

Date of first issue: 09/04/2019

Specific extinguishing meth-

Further information

ods

: Product is compatible with standard fire-fighting agents.

: Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. Use a water spray to cool fully closed containers.

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emergency procedures

Use personal protective equipment. Remove all sources of ignition. Ensure adequate ventilation.

Avoid breathing dust.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Evacuate personnel to safe areas.

Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions

Prevent further leakage or spillage if safe to do so.

Prevent product from entering drains.

Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

Advice on protection against : fire and explosion

Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for nonconductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protec-

tion Association document NFPA 77.

Keep away from open flames, hot surfaces and sources of

ignition.

Use only explosion-proof equipment.

Do not spray on a naked flame or any incandescent material.

Advice on safe handling

Open drum carefully as content may be under pressure.

Avoid formation of aerosol.

Provide sufficient air exchange and/or exhaust in work rooms.



MOTOR MEDIC® AIR BRAKE SYSTEM ANTI-FREEZE & RUST GUARD

Version 1.0 Revision Date: 09/04/2019

SDS Number:

Date of last issue: -

600000001949

Date of first issue: 09/04/2019

Do not breathe vapours/dust.

Do not smoke.

Take precautionary measures against static discharges. Dispose of rinse water in accordance with local and national

regulations.

Container hazardous when empty.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

For personal protection see section 8.

Conditions for safe storage

Keep container tightly closed in a dry and well-ventilated

place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage. Observe label precautions.

No smoking.

Further information on stor-

age stability

: No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis	
Methanol	67-56-1	TWA	200 ppm	ACGIH	
		STEL	250 ppm	ACGIH	
		TWA	200 ppm 260 mg/m3	NIOSH REL	
		ST	250 ppm 325 mg/m3	NIOSH REL	
		TWA	200 ppm 260 mg/m3	OSHA Z-1	
		STEL	250 ppm 325 mg/m3	OSHA P0	
		TWA	200 ppm 260 mg/m3	OSHA P0	

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentra-tion	Basis
Methanol	67-56-1	Methanol	Urine	End of shift (As soon as possible after exposure ceases)	15 mg/l	ACGIH BEI

Engineering measures

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if



MOTOR MEDIC® AIR BRAKE SYSTEM ANTI-FREEZE & RUST GUARD

Version 1.0 Revision Date: 09/04/2019

SDS Number: 60000001949

Date of last issue: -

Date of first issue: 09/04/2019

applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Hand protection

Remarks : Wear resistant gloves (consult your safety equipment suppli-

er). The suitability for a specific workplace should be discussed with the producers of the protective gloves. Discard

gloves that show tears, pinholes, or signs of wear.

Eye protection : Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eyes.

Skin and body protection : Choose body protection according to the amount and con-

centration of the dangerous substance at the work place.

Wear as appropriate: Impervious clothing Flame-resistant clothing

Safety shoes

Remove and wash contaminated clothing before re-use.

Hygiene measures : Handle in accordance with good industrial hygiene and safety

practice

Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling

the product.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : blue

Odour : pungent

Odour Threshold : not determined

pH : not determined

Melting point/freezing point : not determined

Boiling point/boiling range : 64.7 °C

(1013.250 hPa)

Value for Component

Flash point : 12 °C

Method: closed cup Value for Component

Evaporation rate : not determined

Flammability (solid, gas) : No data available



MOTOR MEDIC® AIR BRAKE SYSTEM ANTI-FREEZE & RUST GUARD

Version 1.0 Revision Date: 09/04/2019

SDS Number: 600000001949

Date of last issue: -

Date of first issue: 09/04/2019

Self-ignition

: not determined

Upper explosion limit / Upper

flammability limit

not determined

Lower explosion limit / Lower :

flammability limit

not determined

Vapour pressure : not determined

Relative vapour density : not determined

Density : 0.7922 g/cm3

Solubility(ies)

Water solubility : completely miscible

Partition coefficient: n-

octanol/water

not determined

Decomposition temperature

not determined

Viscosity

Viscosity, dynamic

not determined

Viscosity, kinematic

not determined

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity

No decomposition if stored and applied as directed.

Chemical stability

No decomposition if stored and applied as directed.

Possibility of hazardous reac-

tions

No decomposition if stored and applied as directed.

Vapours may form explosive mixture with air.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

: Strong oxidizing agents

Hazardous decomposition

products

.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Eye contact Skin contact Ingestion



MOTOR MEDIC® AIR BRAKE SYSTEM ANTI-FREEZE & RUST GUARD

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/04/2019 600000001949 Date of first issue: 09/04/2019

Acute toxicity

Toxic if swallowed, in contact with skin or if inhaled.

Product:

Acute oral toxicity : Acute toxicity estimate: 100.15 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: 300.45 mg/kg

Method: Calculation method

Components:

Methanol:

Acute oral toxicity : LDLo (Humans): 300 mg/kg

Assessment: The component/mixture is toxic after single in-

gestion.

Acute inhalation toxicity : Test atmosphere: dust/mist

Assessment: The component/mixture is toxic after short term

inhalation.

Acute dermal toxicity : LD50 (Rabbit): 12,800 mg/kg

Assessment: The component/mixture is toxic after single con-

tact with skin.

Skin corrosion/irritation

Not classified based on available information.

Components:

Methanol:

Species: Rabbit

Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

Methanol:

Species: Rabbit

Result: Possibly irritating to eyes



MOTOR MEDIC® AIR BRAKE SYSTEM ANTI-FREEZE & RUST GUARD

Version Revision Date: SDS Number: Date of last issue: -

1.0 09/04/2019 60000001949 Date of first issue: 09/04/2019

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Methanol:

Test Type: Maximisation Test

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Method: OECD Test Guideline 406

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Causes damage to organs (Central nervous system, Eyes).

Components:

Methanol:

Target Organs: Central nervous system, Eyes

Assessment: The substance or mixture is classified as specific target organ toxicant, single ex-

posure, category 1.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks: No data available



MOTOR MEDIC® AIR BRAKE SYSTEM ANTI-FREEZE & RUST GUARD

Version 1.0 Revision Date:

SDS Number:

Date of last issue: -

09/04/2019 60000001949

Date of first issue: 09/04/2019

SECTION 12. ECOLOGICAL INFORMATION

Toxicity

Additional ecological

information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Dangerous goods descriptions (if indicated below) may not reflect quantity, end-use, or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

International Regulations

IATA-DGR

UN/ID No. : UN 1230
Proper shipping name : Methanol

Class : 3
Subsidiary risk : 6.1
Packing group : II
Labels : 3 (6.1)
Packing instruction (cargo : 364

aircraft)

IMDG-Code

UN number : UN 1230 Proper shipping name : METHANOL

 Class
 : 3

 Subsidiary risk
 : 6.1

 Packing group
 : II

 Labels
 : 3 (6.1)

 EmS Code
 : F-E, S-D

 Marine pollutant
 : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR



MOTOR MEDIC® AIR BRAKE SYSTEM ANTI-FREEZE & RUST GUARD

Version 1.0 Revision Date:

SDS Number:

Date of last issue: -

09/04/2019 60000001949

Date of first issue: 09/04/2019

UN/ID/NA number Proper shipping name : UN 1230 : Methanol

Class Packing group Labels ERG Code

Marine pollutant

: 3 : II : 3 : 131

: no

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Methanol	67-56-1	100	100 (F003)
Xylene	1330-20-7	100	100 (F003)
Ethylbenzene	100-41-4	100	100 (F003)
Methanol	67-56-1	5000	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards

: Flammable (gases, aerosols, liquids, or solids)

Acute toxicity (any route of exposure)

Specific target organ toxicity (single or repeated exposure)

SARA 313

The following components are subject to reporting levels es-

tablished by SARA Title III, Section 313:

Methanol

67-56-1

>= 90 - <= 100 %

California Prop. 65

WARNING: This product can expose you to chemicals including Ethylbenzene, which is/are known to the State of California to cause cancer, and Methanol, Toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



MOTOR MEDIC® AIR BRAKE SYSTEM ANTI-FREEZE & RUST GUARD

Version 1.0 Revision Date: 09/04/2019

SDS Number: 600000001949


Date of last issue: -

Date of first issue: 09/04/2019

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard.

Revision Date

: 09/04/2019

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN