

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name

: Valvoline™ NON-DETERGENT SAE 30 MOTOR OIL

Recommended use of the chemical and restrictions on use

Details of the supplier of the safety data sheet	Emergency telephone number 1-800-VALVOLINE
Valvoline LLC 3499 Blazer Parkway Lexington, KY 40509	Regulatory Information Number 1-800-TEAMVAL
United States of America	Product Information 1-800-TEAMVAL
SDS@valvoline.com	

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

GHS Label element

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
RESIDUAL OILS (PETROLEUM),			15.05
SOLVENT-DEWAXED		substance or mixture.	

Revision Date: 07/31/2016
Print Date: 11/1/2016
SDS Number: R0169702
Version: 1.2
-

SECTION 4. FIRST AID MEASUR	ES
General advice	: No hazards which require special first aid measures.
If inhaled	 If breathed in, move person into fresh air. If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	: First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
In case of eye contact	: Remove contact lenses. Protect unharmed eye.
If swallowed	: Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician.
Most important symptoms and effects, both acute and delayed	: Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea) irritation (nose, throat, airways) Dizziness
Notes to physician	: No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	 Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray Foam Carbon dioxide (CO2) Dry chemical
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: carbon dioxide and carbon monoxide Hydrocarbons
Specific extinguishing	:



	L
Valvoline [™] NON-DETERGENT SAE 30 MOTOR OIL	I
	I
822382	l

methods

		Product is compatible with standard fire-fighting agents.
Further information	:	Standard procedure for chemical fires.
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	Persons not wearing protective equipment should be from area of spill until clean-up has been completed.	
Environmental precautions	Prevent further leakage or spillage if safe to do so.	
Methods and materials for containment and cleaning up	Soak up with inert absorbent material (e.g. sand, silic acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.	a gel,
Other information	Comply with all applicable federal, state, and local re	gulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	 Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8.
Conditions for safe storage	: Electrical installations / working materials must comply with the technological safety standards.
Materials to avoid	: No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
RESIDUAL OILS (PETROLEUM), SOLVENT- DEWAXED	64742-62-7	PEL	500 ppm 2,000 mg/m3	OSHA_TRA NS
		REL	5 mg/m3 Mist.	NIOSH/GUID E

Valvoline.	Page: 4
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0169702
Valvoline [™] NON-DETERGENT SAE 30 MOTOR OIL	Version: 1.2
822382	

		STEL PEL	10 mg/m3 Mist. 5 mg/m3 Mist.	NIOSH/GUID E OSHA_TRA NS
Engineering measures	conditions exist, prov exhaust) guidelines	General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.		
Personal protective equipme	ent			
Respiratory protection	: No person required.	nal respiratory prote	ctive equipment norm	nally
Eye protection		ety goggles if materi	nditions of use. Wea al could be misted or	
Skin and body protection	: Wear as a Safety sh Wear resi supplier).	oes	lt your safety equipme	ent
Hygiene measures	: General i	ndustrial hygiene pr	actice.	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: liquid
Colour	: amber
Odour	: No data available
Odour Threshold	: No data available
рН	: No data available
Melting point/freezing point	: No data available
Boiling point/boiling range	: 424.99 °F / 218.33 °C (1,013.333333 hPa)
Flash point	Calculated Phase Transition Liquid/Gas : > 390 °F / > 199 °C Method: Cleveland open cup
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available



Revision Date: 07/31/2016

Valvoline[™] NON-DETERGENT SAE 30 MOTOR OIL 822382

 Print Date: 11/1/2016

 SDS Number: R0169702

 30 MOTOR OIL
 Version: 1.2

Upper explosion limit	:	6 %(V) GLP: Calculated Explosive Limit
Lower explosion limit	:	1 %(V) GLP: Calculated Explosive Limit
Vapour pressure	:	1.33333333 hPa (20 °C) Calculated Vapor Pressure
Relative vapour density	:	< 1AIR=1
Relative density	:	0.888 (15.6 °C)
Density	:	0.8890 g/cm3 (15.56 °C)
Solubility(ies) Water solubility	:	negligible
Solubility in other solvents	:	No data available
Partition coefficient: n- octanol/water	:	No data available
Thermal decomposition	:	
		No data available
Viscosity Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Oxidizing properties	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: Stable under recommended storage conditions.
Possibility of hazardous reactions	Product will not undergo hazardous polymerization.
Incompatible materials	: Strong oxidizing agents
Hazardous decomposition products	carbon dioxide and carbon monoxide

Valvoline	Page: 6
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0169702
Valvoline [™] NON-DETERGENT SAE 30 MOTOR OIL	Version: 1.2
822382	

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of : exposure	Inhalation Skin contact Eye Contact Ingestion
Acute toxicity Not classified based on available <u>Components:</u> RESIDUAL OILS (PETROLEUM Acute oral toxicity	
Acute inhalation toxicity :	LC50 (Rat): > 5.58 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: Not classified as acutely toxic by inhalation under GHS. Remarks: No mortality observed at this dose.
Acute dermal toxicity :	LD 50 (Rabbit): > 5,000 mg/kg Remarks: No mortality observed at this dose.
	LD 50 (Rabbit): > 2,000 mg/kg Assessment: Not classified as acutely toxic by dermal absorption under GHS.

Skin corrosion/irritation

Not classified based on available information. **Product:**

Result: Repeated exposure may cause skin dryness or cracking.

Components:

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED: Species: Rabbit Result: Not irritating to skin

Serious eye damage/eye irritation

Not classified based on available information. <u>Product:</u> Remarks: Unlikely to cause eye irritation or injury.

Components:

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED: Species: Rabbit Result: Not irritating to eyes

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.



Revision Date: 07/31/2016

Print Date: 11/1/2016

SDS Number: R0169702 Version: 1.2

Valvoline[™] NON-DETERGENT SAE 30 MOTOR OIL

822382

Components:

RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED: Test Type: Buehler Test Species: Guinea pig Assessment: Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified based on available information. **Carcinogenicity** Not classified based on available information. **Reproductive toxicity** Not classified based on available information. **STOT - single exposure** Not classified based on available information. **STOT - repeated exposure** Not classified based on available information. **Aspiration toxicity** Not classified based on available information. **Components:** RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED: No aspiration toxicity classification

Further information Product:

Remarks: No data available

Carcinogenicity: IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:			
RESIDUAL OILS (PETROLEUM), SOLVENT-DEWAXED:			
Toxicity to fish :	LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 203		



Revision Date: 07/31/2016

Print Date: 11/1/2016

SDS Number: R0169702 Version: 1.2

Valvoline™ NON-DETERGENT SAE 30 MOTOR OIL

822382

Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates	 EL50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202
Toxicity to algae	 NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	: NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated >= 1,000 mg/l Exposure time: 14 d
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	 NOEL (Daphnia (water flea)): 10 mg/l Exposure time: 21 d Test substance: WAF Method: OECD Test Guideline 211
Persistence and degradability	,
Components:	
RESIDUAL OILS (PETROLEUN	
Biodegradability	 Result: Not readily biodegradable. Biodegradation: 2 - 4 % Exposure time: 28 d Method: OECD Test Guideline 301B
Bioaccumulative potential	
Components:	
No data available	
Mobility in soil	
<u>Components:</u> No data available	
Other adverse effects	
No data available	
Product:	

Product: Additional ecological information

: No data available

Components:

Valvoline.	Page: 9
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0169702
Valvoline [™] NON-DETERGENT SAE 30 MOTOR OIL	Version: 1.2
822382	

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
General advice	: Dispose of in accordance with all applicable local, state and federal regulations.
Contaminated packaging	: Empty remaining contents.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION					
ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

Valvoline.	Page: 10
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0169702
Valvoline [™] NON-DETERGENT SAE 30 MOTOR OIL	Version: 1.2
822382	

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	no

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards	:	No SARA Hazards
SARA 313 Component(s)SARA 313	:	This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.
California Prop 65		Proposition 65 warnings are not required for this product based on the results of a risk assessment.
The components of this proc TSCA		et are reported in the following inventories: On TSCA Inventory
DSL	:	All components of this product are on the Canadian DSL.
AUSTR	:	On the inventory, or in compliance with the inventory
ENCS	:	On the inventory, or in compliance with the inventory
KECL	:	On the inventory, or in compliance with the inventory
PICCS	:	On the inventory, or in compliance with the inventory
IECSC	:	On the inventory, or in compliance with the inventory

Inventories


AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TSCA (USA)

Valvoline.	Page: 11
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 11/1/2016
	SDS Number: R0169702
Valvoline [™] NON-DETERGENT SAE 30 MOTOR OIL	Version: 1.2
822382	

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 07/31/2016



NFPA Flammable and Combustible Liquids Classification Combustible Liquid Class IIIB

Full text of H-Statements referred to under sections 2 and 3.H315Causes skin irritation.

Further information

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-825-8654).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals. H-statement : Hazard Statement



Revision Date: 07/31/2016

Print Date: 11/1/2016 SDS Number: R0169702

Version: 1.2

Valvoline[™] NON-DETERGENT SAE 30 MOTOR OIL

822382

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization" IMDG : International Maritime Code for Dangerous Goods ISO : International Organization for Standardization logPow : octanol-water partition coefficient LCxx : Lethal Concentration, for xx percent of test population LDxx : Lethal Dose, for xx percent of test population. ICxx : Inhibitory Concentration for xx of a substance Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified OECD : Organization for Economic Co-operation and Development **OEL** : Occupational Exposure Limit P-Statement : Precautionary Statement PBT : Persistent , Bioaccumulative and Toxic **PPE : Personal Protective Equipment** STEL : Short-term exposure limit STOT : Specific Target Organ Toxicity TLV : Threshold Limit Value TWA : Time-weighted average vPvB : Very Persistent and Very Bioaccumulative WEL : Workplace Exposure Level CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act DOT : Department of Transportation FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act HMIRC : Hazardous Materials Information Review Commission HMIS : Hazardous Materials Identification System

NFPA : National Fire Protection Association

NIOSH : National Institute for Occupational Safety and Health

OSHA : Occupational Safety and Health Administration

PMRA : Health Canada Pest Management Regulatory Agency

RTK : Right to Know

WHMIS : Workplace Hazardous Materials Information System