

SAFETY DATA SHEET

Issue Date 23-Oct-2015 Revision Date 27-Sept-2019 Version 1

1. IDENTIFICATION

Product identifier

Product Name XL-8 Green

Other means of identification

Product Code CPDXL8

UN/ID no. Paint, 3, UN 1263, II Synonyms Solvent Based Paint

Recommended use of the chemical and restrictions on use

Recommended Use Restricted to professional users.

Uses advised against Consumer use.

Details of the supplier of the safety data sheet

Manufacturer Address

GS Plastics, LLC 23580 Craigs Creek Rd New Castle, VA 24127 http://www.gsplasticsllc.com

Emergency telephone number

Company Phone Number 1-276-629-7981

Emergency Telephone ChemTel Inc. 1-800-255-3924 - Toll Free North America 800-255-3924 or International

+01-813-248-0585

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Inhalation (Dusts/Mists)	Category 4	
Serious eye damage/eye irritation	Category 2A	
Carcinogenicity	Category 2	
Specific target organ toxicity (single exposure)	Category 3	
Flammable liquids	Category 2	

Label elements

Emergency Overview

Danger

Hazard statements

Harmful if inhaled

Causes serious eye irritation Suspected of causing cancer

May cause respiratory irritation. May cause drowsiness or dizziness

Highly flammable liquid and vapor



Appearance Thick

Physical state Liquid

Odor Solvent

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Avoid breathing fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Wash face, hands and any exposed skin thoroughly after handling

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ ventilating / lighting / equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention

IF IN EYES: Irrigate with flowing water immediately and continuously for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing and consult with medical professional for further treatment.

If eye irritation persists: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

May be harmful if swallowed Harmful to aquatic life with long lasting effects

Unknown acute toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

<u>Mixture</u> This mixture has not been evaluated as a whole. Information provided on the health effects of this product is based on individual components.

Synonyms

Solvent Based Paint.

Chemical Name	CAS No.	Weight-%	Trade Secret
Methyl ethyl ketone	78-93-3	30 - 60	*
Methylisobutyl ketone	108-10-1	10 - 30	*
Cyclohexanone	108-94-1	1 - 5	*

4. FIRST AID MEASURES

Description of first aid measures

Eye contact If symptoms develop, immediately move individual away from exposure and into fresh air.

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek

immediate medical attention/advice.

Skin contact Remove contaminated clothing. Wash exposed area with soap and water. If symptoms

persist, seek medical attention. Launder clothing before reuse.

Inhalation Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult.

qualified personnel should give oxygen. Keep person warm and quiet; seek immediate

medical attention.

Ingestion Seek medical attention. If individual is drowsy or unconscious, do not give anything by

mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible,

do not leave individual unattended.

Most important symptoms and effects, both acute and delayed

Symptoms May irritate, cause redness and pain.

Indication of any immediate medical attention and special treatment needed

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Foam, alcohol foam, CO2, dry chemical, water fog.

Unsuitable extinguishing media CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, other flames and ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

Hazardous combustion products Carbon dioxide (CO2). Carbon monoxide. Formaldehyde. Unidentified organic compounds.

Explosion data

Sensitivity to Mechanical Impact No information available. Sensitivity to Static Discharge No information available.

Protective equipment and precautions for firefighters

Water may be innefective. Water may be used to keep fire-exposed containers cool until fire is out. Wear a self-contained breathing apparatus with a full facepiece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation, especially in confined areas.

Other Information Eliminate all sources of ignition such as flares, flames (including pilot lights), and electrical

sparks. Persons not wearing protective equipment should be excluded from area of spill

until clean-up has been completed.

Environmental precautions

Environmental precautions

See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for containment

Stop spill at source. Prevent from entering drains, sewers, streams or other bodies of water. Prevent from spreading. If runoff occurs, notify authorities as required. Pump or vacuum transfer spilled product to clean containers for recovery. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal. Note: Use only non-sparking equipment to clean up spill.

Methods for cleaning up

Absorb liquid on vermiculite, floor absorbent or other absorbent material. Scoop or scrape up using non-sparking equipment. Put container for recovery or disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. All five-gallon pails and larger metal containers should be grounded and/or bonded when material is transferred. Warning: Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperatures and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without the presence of obvious ignition sources. Published "auto-ignition" or "ignition" temperature values cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Any use of this product in elevated temperature processes should be thoroughly evaluated to establish and maintain safe operating conditions.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Avoid exposure to heat sources such as direct sunlight or steam pipes.

Incompatible materials

Avoid contact with strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Methyl ethyl ketone	STEL: 300 ppm	TWA: 200 ppm	IDLH: 3000 ppm
78-93-3	TWA: 200 ppm	TWA: 590 mg/m ³	TWA: 200 ppm
		(vacated) TWA: 200 ppm	TWA: 590 mg/m ³
		(vacated) TWA: 590 mg/m ³	STEL: 300 ppm
		(vacated) STEL: 300 ppm	STEL: 885 mg/m ³
		(vacated) STEL: 885 mg/m ³	
Methylisobutyl ketone	STEL: 75 ppm	TWA: 100 ppm	IDLH: 500 ppm
108-10-1	TWA: 20 ppm	TWA: 410 mg/m ³	TWA: 50 ppm
		(vacated) TWA: 50 ppm	TWA: 205 mg/m ³
		(vacated) TWA: 205 mg/m ³	STEL: 75 ppm
		(vacated) STEL: 75 ppm	STEL: 300 mg/m ³
		(vacated) STEL: 300 mg/m ³	
Cyclohexanone	STEL: 50 ppm	TWA: 50 ppm	IDLH: 700 ppm
108-94-1	TWA: 20 ppm	TWA: 200 mg/m ³	TWA: 25 ppm
	S*	(vacated) TWA: 25 ppm	TWA: 100 mg/m ³
		(vacated) TWA: 100 mg/m ³	. 0
		(vacated) S*	

Appropriate engineering controls

Engineering Controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain

exposure below TLV(s).

Individual protection measures, such as personal protective equipment

Eye/face protection Chemical splash goggles in compliance with OSHA regulations are advised; however.

OSHA regulations also permit other type safety glasses. Consult your safety

representative.

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, Skin and body protection

as appropriate, to prevent skin contact.

Respiratory protection If workplace exposure limit(s) of product or any component is exceeded (see exposure

guidelines), a NIOSH/MSHA approved air supplied respirator is advised in absence of proper environmental control. OSHA regulations also permit other NIOSH/MSHA respirators (negative pressure type) under specified conditions (see your industrial hygienist). Engineering or administrative controls should be implemented to reduce

exposure.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid

Appearance

Thick Color All Colors (Except Greent)

Odor threshold

Odor Solvent

CC (closed cup)

No information available

Property Values Remarks • Method

No information available

pН No information available

Melting point / freezing point No information available

Boiling point / boiling range 79.444 °C

Flash point -6.11 °C 21 °F **Evaporation rate** Slower than Ether

Flammability (solid, gas) No information available Flammability Limit in Air

Upper flammability limit: No information available Lower flammability limit: No information available Vapor pressure No information available

Vapor density Heavier than air Relative density 7.64 LB/GL

Water solubility No information available Solubility in other solvents No information available Partition coefficient No information available **Autoignition temperature** No information available **Decomposition temperature** No information available No information available Kinematic viscosity Dynamic viscosity No information available **Explosive properties** No information available

Other Information

Oxidizing properties

Softening point No information available Molecular weight No information available

VOC Content (%)

Density No information available **Bulk density** No information available

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Incompatible materials.

Incompatible materials

Avoid contact with strong oxidizing agents.

Hazardous Decomposition Products

Carbon monoxide. Carbon dioxide (CO2). Formaldehyde. Unidentified organic compounds.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information PRIMARY ROUTES OF EXPOSURE: Inhalation, Skin & Eye Contact from liquid, vapors

or aerosols.

Inhalation May be harmful if inhaled.

Eye contact Causes serious eye irritation.

Skin contact Prolonged or repeated skin contact may cause drying, cracking, or irritation.

Ingestion None known.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Methyl ethyl ketone 78-93-3	= 2737 mg/kg (Rat)= 2483 mg/kg (Rat)	= 5000 mg/kg (Rabbit) = 6480 mg/kg (Rabbit)	= 11700 ppm (Rat) 4 h
Methylisobutyl ketone 108-10-1	= 2080 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	= 8.2 mg/L (Rat) 4 h
Cyclohexanone 108-94-1	= 1544 mg/kg (Rat)	= 947 mg/kg (Rabbit)	= 8000 ppm (Rat) 4 h

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

SensitizationNo information available.Germ cell mutagenicityNo information available.CarcinogenicityNo information available.

 Chemical Name
 ACGIH
 IARC
 NTP
 OSHA

 Methylisobutyl ketone
 A3
 Group 2B
 X

 108-10-1
 Cyclohexanone
 A3
 Group 3

 108-94-1

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
Aspiration hazard

No information available.
No information available.
No information available.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

 ATEmix (oral)
 4,476.00

 ATEmix (dermal)
 5,327.00

 ATEmix (inhalation-dust/mist)
 3.36

 ATEmix (inhalation-vapor)
 18,480.00

12. ECOLOGICAL INFORMATION

Ecotoxicity

0 % of the mixture consists of components(s) of unknown hazards to the aquatic environment

Chemical Name	Algae/aquatic plants	Fish	Crustacea
Cyclohexanone 108-94-1	20: 96 h Chlorella vulgaris mg/L EC50	481 - 578: 96 h Pimephales promelas mg/L LC50 flow-through 8.9: 96 h Pimephales promelas mg/L LC50	800: 24 h Daphnia magna mg/L EC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical Name	Partition coefficient
Methyl ethyl ketone 78-93-3	0.29
Methylisobutyl ketone 108-10-1	1.19
Cyclohexanone 108-94-1	0.86

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Empty containers retain product residue; observe all precautions for product. Do not heat

or cut empty container with electric or gas torch because highly toxic vapors and gases are formed. Do not reuse without thorough commercial cleaning and reconditioning. If container is to be disposed, ensure all product residues are removed prior to disposal.

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Cyclohexanone	-	Included in waste stream:	-	U057
108-94-1		F039		

Chemical Name	California Hazardous Waste Status
Methyl ethyl ketone	Toxic
78-93-3	Ignitable

14. TRANSPORT INFORMATION

DOT

UN/ID no. Paint, 3, UN 1263, II Proper shipping name Flammable liquid

15. REGULATORY INFORMATION

International Inventories

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
Methylisobutyl ketone - 108-10-1	1.0
SARA 311/312 Hazard Categories	•
Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Methyl ethyl ketone	5000 lb	-	RQ 5000 lb final RQ
78-93-3			RQ 2270 kg final RQ
Methylisobutyl ketone	5000 lb	-	RQ 5000 lb final RQ
108-10-1			RQ 2270 kg final RQ
Cyclohexanone	5000 lb	-	RQ 5000 lb final RQ
108-94-1			RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
Methylisobutyl ketone - 108-10-1	Carcinogen
	Developmental

U.S. State Right-to-Know Regulations

This product contains the following substance(s) regulated by state right-to-know regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Methyl ethyl ketone 78-93-3	X	Х	X
Methylisobutyl ketone 108-10-1	Х	X	Х
Cyclohexanone 108-94-1	Х	Х	Х

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 2 Flammability 3 Instability 0 Physical and Chemical

HMIS Health hazards 0 Flammability 0 Physical hazards 0 Personal protection -

Prepared By GS Plastics, LLC Issue Date 23-Oct-2015

Revision Date 27-Sept-2019

Revision Note

No information available

Disclaimer

The information in this Safety Data Sheet should be provided to all who will u se, handle, store, transport, or otherwise be exposed to this product. The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

End of Safety Data Sheet