		Page: 1
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0321818
Valvoline™ HD SAE 75W-90 SYNTHETIC GEAR OIL		Version: 1.2
VV700285M		

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Valvoline™ HD SAE 75W-90 SYNTHETIC GEAR OIL

Recommended use of the chemical and restrictions on use


Details of the supplier of the safety data sheet Valvoline LLC 3499 Blazer Parkway Lexington, KY 40509 United States of America SDS@valvoline.com	Emergency telephone number 1-800-VALVOLINE Regulatory Information Number 1-800-TEAMVAL Product Information 1-800-TEAMVAL
---	--

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Skin sensitization : Category 1

GHS Label element

Hazard pictograms : 

Signal Word : Warning


Hazard Statements : May cause an allergic skin reaction.

Precautionary Statements : If medical advice is needed, have product container or label at hand.
Keep out of reach of children.
Read label before use.

Prevention:

Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves.

Response:

		Page: 2
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0321818
Valvoline™ HD SAE 75W-90 SYNTHETIC GEAR OIL		Version: 1.2
VV700285M		

IF ON SKIN: Wash with plenty of soap and water.
 If skin irritation or rash occurs: Get medical advice/ attention.
 Wash contaminated clothing before reuse.
Disposal:
 Dispose of contents/ container to an approved waste disposal plant.

Other hazards
 None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components


Chemical Name	CAS-No.	Classification	Concentration (%)
OLEFINSULFIDE	68937-96-2	Skin Sens. 1B; H317 Aquatic Chronic 3; H412	5.00
N-PHENYL-1-NAPHTHYLAMINE	90-30-2	Acute Tox. 4; H302 Skin Sens. 1; H317 STOT RE 2; H373	0.99

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
 Show this safety data sheet to the doctor in attendance.
 Do not leave the victim unattended.

If inhaled : If breathed in, move person into fresh air.
 If unconscious place in recovery position and seek medical advice.
 If symptoms persist, call a physician.

In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.

		Page: 3
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0321818
Valvoline™ HD SAE 75W-90 SYNTHETIC GEAR OIL		Version: 1.2
VV700285M		


If on skin, rinse well with water.
 First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
 Wash contaminated clothing before re-use.

- In case of eye contact : Flush eyes with water as a precaution.
 Remove contact lenses.
 Protect unharmed eye.
 If eye irritation persists, consult a specialist.
- If swallowed : Do not give milk or alcoholic beverages.
 Never give anything by mouth to an unconscious person.
 If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : May cause an allergic skin reaction.
 No symptoms known or expected.
- Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
 Water spray
 Foam
 Carbon dioxide (CO₂)
 Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide
 oxides of sulfur, nitrogen and phosphorus
 Sulphur oxides
- Specific extinguishing methods :

 Product is compatible with standard fire-fighting agents.
- Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

		Page: 4
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0321818
Valvoline™ HD SAE 75W-90 SYNTHETIC GEAR OIL		Version: 1.2
VV700285M		

SECTION 6. ACCIDENTAL RELEASE MEASURES


- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.
- Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Do not breathe vapours/dust. Do not smoke. Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Container hazardous when empty. Avoid exposure - obtain special instructions before use. Avoid contact with skin and eyes. Smoking, eating and drinking should be prohibited in the application area. For personal protection see section 8. Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

		Page: 5
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0321818
Valvoline™ HD SAE 75W-90 SYNTHETIC GEAR OIL VV700285M		Version: 1.2

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Wear as appropriate:
impervious clothing
Safety shoes
Choose body protection according to the amount and concentration of the dangerous substance at the work place. Discard gloves that show tears, pinholes, or signs of wear. Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures : Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : liquid

Colour : amber

Odour : pungent

Odour Threshold : No data available

pH : No data available


:
No data available

: No data available

Flash point : 419 °F / 215 °C
Method: Closed Cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

		Page: 6
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0321818
Valvoline™ HD SAE 75W-90 SYNTHETIC GEAR OIL		Version: 1.2
VV700285M		

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : 0.879 g/cm³ (15.56 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 122 mm²/s (40 °C)

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.


Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Conditions to avoid : excessive heat

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products : carbon dioxide and carbon monoxide
oxides of sulfur, nitrogen and phosphorus
Sodium oxides

		Page: 7
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0321818
Valvoline™ HD SAE 75W-90 SYNTHETIC GEAR OIL		Version: 1.2
VV700285M		

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity :
Remarks: Not toxic, not known to be toxic, not expected to be toxic by Ingestion

Acute inhalation toxicity : Remarks: Not toxic, not known to be toxic, not expected to be toxic by Inhalation
Mild respiratory irritant

Components:

N-PHENYL-1-NAPHTHYLAMINE:

Acute oral toxicity : LD 50 (Rat, Male): ca. 1,625 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Product:

Result: Not irritating to skin

Remarks: May cause skin irritation in susceptible persons.

Components:

OLEFINSULFIDE:

Result: Mildly irritating to skin

N-PHENYL-1-NAPHTHYLAMINE:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Mildly irritating to skin

Serious eye damage/eye irritation

Not classified based on available information.


Product:

Result: Mildly irritating to eyes

Remarks: Unlikely to cause eye irritation or injury.

Components:

OLEFINSULFIDE:

		Page: 8
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0321818
Valvoline™ HD SAE 75W-90 SYNTHETIC GEAR OIL		Version: 1.2
VV700285M		

Result: Mildly irritating to eyes

N-PHENYL-1-NAPHTHYLAMINE:
 Result: Mildly irritating to eyes
 Method: OECD Test Guideline 405

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.
 Respiratory sensitisation: Not classified based on available information.

Components:

OLEFINSULFIDE:

Assessment: The product is a skin sensitizer, sub-category 1B.

N-PHENYL-1-NAPHTHYLAMINE:
 Test Type: Maximisation Test (GPMT)
 Species: Guinea pig
 Assessment: May cause sensitisation by skin contact.
 Method: OECD Test Guideline 406

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:

N-PHENYL-1-NAPHTHYLAMINE:

Exposure routes: Ingestion

Target Organs: Blood

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks: No data available

Carcinogenicity:

IARC


No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or

		Page: 9
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0321818
Valvoline™ HD SAE 75W-90 SYNTHETIC GEAR OIL		Version: 1.2
VV700285M		

equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

OLEFINSULFIDE:

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

N-PHENYL-1-NAPHTHYLAMINE:

Toxicity to fish : LC 50 (Oncorhynchus mykiss (rainbow trout)): 0.44 - 0.74 mg/l
Exposure time: 96 h
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates : EC 50 (Water flea (Daphnia magna)): 0.3 - 0.68 mg/l
Exposure time: 48 h
Test Type: static test

Persistence and degradability

Components:

N-PHENYL-1-NAPHTHYLAMINE:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 301C

Bioaccumulative potential

Components:

N-PHENYL-1-NAPHTHYLAMINE:

Partition coefficient: n-octanol/water : log Pow: 4.20

Mobility in soil

Components:


No data available

Other adverse effects

No data available

Product:

Additional ecological : An environmental hazard cannot be excluded in the event of

		Page: 10
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0321818
Valvoline™ HD SAE 75W-90 SYNTHETIC GEAR OIL		Version: 1.2
VV700285M		

information

unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice

: The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging

: Empty remaining contents.
Dispose of as unused product.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

U.S. DOT - ROAD

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS


Not dangerous goods

TDG_ROAD_C

Not dangerous goods

TDG_RAIL_C

Not dangerous goods

		Page: 11
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0321818
Valvoline™ HD SAE 75W-90 SYNTHETIC GEAR OIL		Version: 1.2
VV700285M		

TDG_INWT_C

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

MX_DG

Not dangerous goods

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.


SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : Acute Health Hazard

SARA 313 Component(s)SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Pennsylvania Right To Know

PROPRIETARY SYNTHETIC GEAR LUBRICANT	Not Assigned	90.00 - 100.00 %
MIXTURE OF OLEFIN SULFIDE, H2OP4 ESTER, AMINE SALTS, ALKYL SULFIDE, ALKENYLAMIDE AND OTHER INGREDIENTS	Not Assigned	10.00 - 20.00 %
OLEFINSULFIDE	68937-96-2	5.00 - 10.00 %

		Page: 12
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0321818
Valvoline™ HD SAE 75W-90 SYNTHETIC GEAR OIL VV700285M		Version: 1.2

New Jersey Right To Know

PROPRIETARY SYNTHETIC GEAR LUBRICANT	Not Assigned	90.00 - 100.00 %
MIXTURE OF OLEFIN SULFIDE, H2OP4 ESTER, AMINE SALTS, ALKYL SULFIDE, ALKENYLAMIDE AND OTHER INGREDIENTS	Not Assigned	10.00 - 20.00 %
OLEFINSULFIDE	68937-96-2	5.00 - 10.00 %

California Prop 65


WARNING! This product contains a chemical known to the State of California to cause cancer.
2-NAPHTHALENAMINE 91-59-8

The components of this product are reported in the following inventories:

- TSCA : On TSCA Inventory
- DSL : All components of this product are on the Canadian DSL.
- AICS : Not in compliance with the inventory
- NZIOC : Not in compliance with the inventory
- ENCS : Not in compliance with the inventory
- KECI : Not in compliance with the inventory
- PICCS : Not in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory

Inventories


AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

		Page: 13
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0321818
Valvoline™ HD SAE 75W-90 SYNTHETIC GEAR OIL		Version: 1.2
VV700285M		

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 07/31/2016

<p>NFPA:</p> <div style="text-align: center;"> <p>Flammability</p>  <p>Health Instability</p> <p>Special hazard.</p> </div>	<p>HMIS III:</p> <table border="1" style="width: 100%;"> <tr> <td style="background-color: blue; color: white;">HEALTH</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="background-color: red; color: white;">FLAMMABILITY</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="background-color: yellow;">PHYSICAL HAZARD</td> <td style="text-align: center;">0</td> </tr> </table> <p>0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	1	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	1						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements referred to under sections 2 and 3.


H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.
H373	May cause damage to organs through prolonged or repeated exposure if swallowed.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Further information

Sources of key data used to compile the Safety Data Sheet
Valvoline internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-825-8654).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

		Page: 14
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 11/1/2016
		SDS Number: R0321818
Valvoline™ HD SAE 75W-90 SYNTHETIC GEAR OIL		Version: 1.2
VV700285M		

ACGIH : American Conference of Industrial Hygienists
 BEI : Biological Exposure Index
 CAS : Chemical Abstracts Service (Division of the American Chemical Society).
 CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
 FG : Food grade
 GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
 H-statement : Hazard Statement
 IATA : International Air Transport Association.
 IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
 ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
 IMDG : International Maritime Code for Dangerous Goods
 ISO : International Organization for Standardization
 logPow : octanol-water partition coefficient
 LCxx : Lethal Concentration, for xx percent of test population
 LDxx : Lethal Dose, for xx percent of test population.
 ICxx : Inhibitory Concentration for xx of a substance
 Ecxx : Effective Concentration of xx
 N.O.S.: Not Otherwise Specified
 OECD : Organization for Economic Co-operation and Development
 OEL : Occupational Exposure Limit
 P-Statement : Precautionary Statement
 PBT : Persistent , Bioaccumulative and Toxic
 PPE : Personal Protective Equipment
 STEL : Short-term exposure limit
 STOT : Specific Target Organ Toxicity
 TLV : Threshold Limit Value
 TWA : Time-weighted average
 vPvB : Very Persistent and Very Bioaccumulative
 WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
 DOT : Department of Transportation
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
 HMIRC : Hazardous Materials Information Review Commission
 HMIS : Hazardous Materials Identification System
 NFPA : National Fire Protection Association
 NIOSH : National Institute for Occupational Safety and Health
 OSHA : Occupational Safety and Health Administration
 PMRA : Health Canada Pest Management Regulatory Agency
 RTK : Right to Know
WHMIS : Workplace Hazardous Materials Information System